OF PAC	PAGE 1		SIDE	SET-A	S NOT A SMALL BUSINESS :	x IS IS	THIS RFQ [		TATION RDER)	UEST FOR QUO	REQ (Th
	RATING	UNDER BDSA REG. 2			E REQUEST NO.	3. REQUISITION/PURCHASE REQUEST N					
		MS REG. 1	AND/OR DI	_		05-14	81-50	/03/14	01	4-Q-0066	N00173-1
		TBD	6. DELIVER	ľ			<b>2</b> 72 76	2020 20 1		2000	5a. ISSUED BY
		TBD	7. DELIVERY	-	375-5329			NRL Was		fficer (Code	Supply C
OTHER See Schedule)		DESTINATION	The state of the s		IF NUMBER	TELEPHON	T	ATION CALL (N	JR INFORMA	5b. FC	NAME
Description of the second		9. DESTINA		_		NUMBI	AREA CODE				
		ONSIGNEE	. NAME OF C	la	-0288	767-	202			enthall	Cheryl E
ratory	Labo	Research	Nava					8. TO:			
			o. STREET AD		2		<b>MPANY</b>	b. COM			a. NAME
W Bldg	Ave S	Overlook	100000000000000000000000000000000000000				===			ers	All Quot
			c. CITY	1						SS	c. STREET ADDRE
		ngton									
	20	20375-53				e. STATE f. ZIP CODE					d. CITY
water places	2002		10000						uc I	ISH QUOTATIONS TO TH	10 DI CACE FUIDA
re of	nent to pa Supplies ar	ommit the Governn upplies or service.	est does not o	reque	mation and quotations fu e address in Block 5a. This omission of this quotation I by quoter. Any represent er.	eturn it to the ion of the sub vise indicated	his form and re n the preparati unless otherw	so indicate on t		CE IN BLOCK 5a ON OR LOSE OF BUSINESS	ISSUING OF
			taxes)	ocal	Federal, State and lo	applicable	(Include a	SCHEDULE	11.		
AMOUNT		UNIT PRICE	UNIT		QUANTITY		22-1-270300	S/ SERVICES	SUPPLIE		ITEM NO.
(f)		(e)	(d)		(c)			(b)		Š	(a)
								SHEET	ATION S	SEE CONTINU	
AL END AD DAY	1.0	AD DAVE (III)	- 30 CAL FAIR								
R PERCEN	NUMBER	AR DAYS (%)	c. 30 CALENL		b. 20 CALENDAR DAYS (%)	DAYS	0 CALENDAR E	a. 1 (%)	ENT	FOR PROMPT PAYM	12. DISCOUNT
	_				are not attached.	а	are	ntations	d represer	onal provisions ar	NOTE: Addit
E OF QUOTATION	15. DAT	o	JTHORIZED T		14. SIGNATURE OF PERSO SIGN QUOTATION			F QUOTER	D ADDRESS O	13. NAME AN	a. NAME OF QUO
		5. SIGNER	1							cc	L STREET LOCA
b. TELEPHONE	1			nt)	a NAME (Type or print	-				:55	b. STREET ADDR
AREA CODE			a. NAME (Type of print				11		c. COUNTY		
R	NUMBER			t)	c. TITLE (Type or print)	3.75 - C 7	f. ZIP CODE	e. STATE			d. CITY
ODE	AREA CO	5. SIGNER			a. NAME (Type or print)		f. ZIP CODE	e. STATE	11	ESS	

CONTINUATION SHEET GENERAL SERVICES ADMINISTRATION FED. PROC. REG. (41 CFR) 1-16.101 2 11 N00173-14-Q-0066 NAME OF OFFEROR CONTRACTOR All Quoters ITEM NO. QUANTITY AMOUNT SUPPLIES/SERVICES PRICE 0001 UPS Upgrade Simplified Scope of Supply Ea MGE Galaxy 4000 UPS 40kW, 208V Adjacent Battery Cabinet, 20 min. runtime at 40 kW load Wall Mount Maintenance Bypass Panel 208V, 208V Start-up and assembly service, including I year next business day On site maintenance Installation Service Coordinate and oversee delivery of an APC solution containing a 40 kW UPS system and assorted parts. Coordinate to have APC certified field service technicians set and assemble system. Once electrical work is complete coordinate to have APC certified field service technician start and test system as well as train customer on proper operation. Disconnect and remove feed from existing UPS system back to transformer. Supply and install a 200A fused disconnect, fused to 175A. Supply and install 208V, 175A feed from existing transformer to disconnect within 25'. Supply and install 208V, 175A feed from disconnect to bypass panel within 25', supply and install 208V, 175A feed from bypass panel to UPS within 25' supply and install 208V, 175A feed from UPS back to bypass panel within 25', supply and install 208V, 175A feed from bypass panel to distribution panel within 25'. Optional: Remove and properly dispose of existing MGE Comet UPS system. Ea 1 0002 Environmental Room Chamber operation: Chamber temperature range: 20C to 26C. Chamber temperature control at setpoint +0.1C. Chamber tempeature uniformity: +0.2C@, 23.5C, throughout storage area (with insulated floor) and standard load / Chamber humidity range: 45%RH to 55%RH, elevated humidity only. Chamber humidity control at sensor: +0.5%RH. Approximate 500 to 600 watt heat load. Note: Temperature and relative humidity specifications assume standard operation and a dew-point at or below 50F.

REF. NO. OF DOC. BEING CONT'D

STANDARD FORM 36 JULY 1966

Chamber Construction:

NAME OF OFFEROR CONTRACTOR All Quoters	QUANTITY	-Q-0066	UNIT PRICE	AMC	DUNT
Cont'd  Chamber size, exterior (nominal): 8'W x 12' L x 8' 4" H.  Modular panels are 100% poured-in-place polyurethane constuction, R-Value 31   All panels to incorporate Ecomate polyurethane insulation. This foam has zero Global Warming Potential and zero VOC's without sacrificing thermal efficiency.  Panel surface finish: Interior, embossed white aluminum. 4" urethane insulated ceiling and walls. Exterior surface finish: Embossed white galvanized steel.  Door: Standard 36"x80" swinging(specify location), with keyed entry.  Floor: 4" insulated, smooth aluminum finish.3' long exterior ramp included chamber Controls: Controls to be mounted in an automation control panel located per customer instruction.	QUANTITY	UNIT		AMC	DUNT
Chamber size, exterior (nominal): 8'W x 12' L x 8' 4" H.  Modular panels are 100% poured-in-place polyurethane constuction, R-Value 31+ All panels to incorporate Ecomate polyurethane insulation. This foam has zero Global Warming Potential and zero VOC's without sacrificing thermal efficiency.  Panel surface finish: Interior, embossed white aluminum. 4" urethane insulated ceiling and walls. Exterior surface finish: Embossed white galvanized steel.  Door: Standard 36"x80" swinging(specify location), with keyed entry.  Floor: 4" insulated, smooth aluminum finish.3' long exterior ramp included chamber Controls: Controls to be mounted in an automation control panel located per customer instruction.	QUANTITY	UNIT		AMC	DUNT
Modular panels are 100% poured-in-place polyurethane constuction, R-Value 31+ All panels to incorporate Ecomate polyurethane insulation. This foam has zero Global Warming Potential and zero VOC's without sacrificing thermal efficiency.  Panel surface finish: Interior, embossed white aluminum. 4" urethane insulated ceiling and walls. Exterior surface finish: Embossed white galvanized steel.  Door: Standard 36"x80" swinging(specify location), with keyed entry.  Floor: 4" insulated, smooth aluminum finish.3' long exterior ramp included chamber Controls: Controls to be mounted in an automation control panel located per customer instruction.					
humidity controls NIST traceable temperature sensor with calibration certificate.  Rotronic S2 0.8% RH sensor. Dual display of actual and set point temperature and humidity.  Solid state control relays wherever possible. High and Low Temperature/Humidity Alarms with dry contact remote output, settable in 0.1C and 0.1%RH increments chamber mechanical/Components:  Condensing unit: One top-mounted unit, capable of cooling room to required conditions. Condenser is designed to run at all times to eliminate poor temperature control and uniformity inherent in cycling type systems.  Condensing unit controls temperature of liquid circuit, which circulates through room evaporator/air handler at all times.  Evaporator/Air Handler:Liquid-circuited manufactured by HeatCraft.  Humidifier: Ultrasonic humidification with UV disinfection.  Lighting: Vapor-proof fluorescent lighting. Electrical	<b>Y</b>				

REF, NO. OF DOC. BEING CONT'D PAGE OF STANDARD FORM 36 JULY 1966 CONTINUATION SHEET GENERAL SERVICES ADMINISTRATION FED. PROC. REG. (41 CFR) 1-16,101 2B 11 N00173-14-Q-0066 NAME OF OFFEROR CONTRACTOR All Quoters UNIT AMOUNT ITEM NO. SUPPLIES/SERVICES QUANTITY UNIT PRICE 0003 Additional piping up to 30' from room. Does not include core Ea drilling or unusaul pipe runs 1 Ea 0004 Floor reinforcement to accommodate 500lb cart load. Redundancy--one (additional) Precision Fluid Temperature Ea 0005 Control Unit(PFTCU) with automatic, redundant operation and associated controls/alarms. In the event of interruption to the operation of the on-line refrideration system, a separately circuited refrigeration system shall be activated to maintain constant fluid temperature. Alarms and controls shall perform automatic switching operations and indications. System to include all refrigeration components, pump, heat exchangers, controls, and other items as required to ensure a complete and functional operating package. Room is to be installed on the second floor of facility. If available please include a published price list or a cost breakdown and return the RFQ package to the following fax number (202)767-6678. Any questions concerning this Request for Quotation (RFQ) must be e-mailed to SolQnA@nrl.navy.mil at least five (5) days before the closing date shown in block 10 on page 1 of RFQ.